
产品系列: Ben / 导轨射灯

灯具型号: MBL40515

项目名称:

产品编号:





15°


22°

124

30°










45°

16×60°

Wallwash







产品配件

MP12-15 15°



MP12-22



MP12-30 30°



MP12-45 45°



MP12-EV 16×60°



MP12-EH





MP12-HC 蜂窝网

MP12-BD 四叶片

产品描述

光源类型: LED SMD

温: 2700K/3000K/3500K/4000K(可选)

显色性: Ra 97

色 容 差: ≤2 SDCM

光源寿命: >50000 小时(TM-21 标准)

紫外相对含量: <1µW/lm

蓝光危害: RG1(低风险)

功 率: 15W

光 束 角: 15°/22°/30°/45°/拉伸(16°×60°)/洗墙(可选)

输入电压: 220-240V~ 50/60Hz

控制方式: 单灯旋钮/蓝牙/0-10V/DALI 等调光(可选)

安装方式: 三回路导轨式

角度调节:水平0°~360°,垂直0°~90°

主体材质: 铝合金压铸灯体

表面工艺:静电粉末喷涂;黑色(MBK)/白色(MWT)(可选)

安规认证: CCC

防护等级: IP20

结构工艺: 灯体无外露明线

光学设计: 同一灯具通过手动更换光学透镜改变配光角度